



EZ Node™ Wireless Adapter

Connect one of Maestro's Ethernet devices directly to any wireless Wi-Fi network.

Series = EZ Node™ Wireless Adapter



EZN = EZ Node™ Wireless Adapter

The EZ Node™ Wireless Adapter allows any Maestro product to connect directly to a wireless network.

Enclosure Specifications:
NEMA 4X enclosure;
ABS construction;
Heavy duty aluminum back plate with stainless steel hardware.

1+ = Options (Extend matrix as required)

E = Ethernet, IEEE 802.11b/g/n/ac Wave 2 (WiFi 5) compliant, Passive PoE (Power over Ethernet), 4 X 10/100/1000 Ethernet Interface (RJ-45). Includes 3 dBi Omni-directional antenna, waterproof RJ45 connector, and one 24 VDC power injector for Ethernet based Maestro products. The EZ Node™ is easily configured via web browser, no additional software required. Regulatory approvals: CE/RED, UKCA, CB, EAC, UCRF, RoHS, REACH, CITC, ICASA, ANRT, RCM, NBTC, GITEKI, NTC, FCC, IC, NOM.

SST = Stainless Steel Tag; 8-lines; 2.5" H x 5.5" W

PT = Polyester Tag; 8-lines; 2" H x 4" W

EZN



Options
1+